

AC-DC Selector Guide

5-15 Watts	20-45 Watts	50-70 Watts	80-100 Watts	120-140 Watts	150-180 Watts	200-250 Watts	300-350 Watts	400-600 Watts	650-3000 Watts	LED Drivers	Configurable	DIN Rail
ECL05 • 5 Watts • 2" x 1" x 0.9" • Single Output • Class II • Green Mode	ECP20 • 20 Watts • 2.64" x 1.57" x 0.73" • Single & Dual Output • Class II • Green Mode	VCS50 Q4 • 50 Watts • 4.33" x 3.07" x 1.42" • Single Output • Convection-cooled • Green Mode	VFT80 • 80 Watts • 4" x 2" x 1.1" • Single Output • Class I • Green Mode	SDS120 • 120 Watts • 5" x 3.2" x 1.54" • Single & Multi Outputs • Convection-cooled • Mechanical Options	+ ECP150 Q4 • 150 Watts • 4" x 2" x 1.2" • Single Output (12-48 V) • Built-in Fan Supply • Green Mode	BCC200 • 200 Watts • 9.21" x 4.96" x 1.9" • Single Output • Baseplate-cooled • Remote On/Off	SDF300 • 300 Watts • 5" x 3.2" x 1.5" • Single & Multi Outputs • Fan Cover Options • Remote On/Off	BCC400 • 400 Watts • 9.2" x 4.9" x 1.9" • Single Output • Baseplate-cooled • Remote On/Off	+ SHP/MHP650 • 650 Watts • 8" x 4" x 2.5" • Single Output • Remote On/Off • Mechanical Options	DLA50 • 50 Watts • 7.2" x 1.6" 1.3" • Single Output • Up to 88% Efficiency • IP67	+ LP/LP MD • 250-450 Watts • Single & Multi Outputs • Low Profile 1U • Semi F47 Compliant • Isolated Outputs	DNR05-60 • 5 - 60 Watts • Up to 89% Efficiency • Single Output • Convection-cooled • DC Standby Versions
VCP05 • 5 Watts • 2.3" x 1.4" x 0.85" • Single Output • Class II • Green Mode	+ VCP24 • 24 Watts • 2.91" x 1.64" x 1" • Single Output • Class II • Green Mode	+ ECM60 • 60 Watts • 4" x 2" x 1.2" • Single & Multi Outputs • Class I & II • Convection-cooled	ECC100 • 100 Watts • 5" x 4.1" x 1.8" • Single Output • Baseplate-cooled • Remote On/Off	CLC125 • 125 Watts • 4" x 2" x 1.2" • Single Output • Fan Output • Green Mode	LCL150 • 150 Watts • 7.55" x 3.74" x 1.97" • Single Output • Convection-cooled • Low Cost	+ PBM200 • 200 Watts • 7" x 4" x 1.5" • Single & Multi Outputs • Remote On/Off • Mechanical Options	SMQ300 • 300 Watts • 8" x 4" x 2" • Single Output • Mechanical Options • Remote On/Off	+ FCM400 • 400 Watts • 6" x 4" x 1.93" • Single Output • Low Noise Fan • 5V Standby	HCP650/1000 • 650/1000 Watts • Single Output • Programmable Voltage • Programmable Current • Controls and Alarms	DLA75 • 75 Watts • 8.3" x 2.6" 1.4" • Single Output • Up to 93% Efficiency • IP67	+ flexPower • 400-2400 Watts • Single & Multi Outputs • Semi F47 Compliant • Extra Power at High Line • Isolated Outputs	DRS80-240 • 80 - 240 Watts • Up to 92% Efficiency • Single Output • Convection-cooled • Ultra Slim Package
ECL10 • 10 Watts • 2" x 1" x 0.9" • Single Output • Class II • Green Mode	ECL25 • 25 Watts • 3" x 1.4" x 1" • Single Output • Class II • Green Mode	SDS60 • 60 Watts • 5" x 3" x 1.32" • Single & Multi Outputs • Class I • Non-Std O/P's Available	+ ECM100 • 100 Watts • 4.5" x 2.5" x 1.2" • Single & Multi Outputs • Class I & II • PoE Version	+ JPS130 • 130 Watts • 5" x 3" x 1.34" • Single & Multi Outputs • Fan Output • Convection Rating	+ SDS150 • 150 Watts • 5" x 3.2" x 1.62" • Single Output • Convection-cooled • Mechanical Options	EMA212 • 212 Watts • 5" x 3" x 1.34" • Single Output • Fan Output • Remote On/Off	LCL300 • 300 Watts • 8.07" x 4.33" x 1.97" • Single Output • Remote On/Off • Low Cost	+ SMM400 • 400 Watts • 8" x 5" x 1.6" • Single & Multi Outputs • Current Share Option • Mechanical Options	SMR800 • 800 Watts • 9.1" x 4.2" x 2.5" • Single Output • SEMI F47 Compliant • Remote On/Off	DLA120 • 120 Watts • 8.7" x 2.6" 1.4" • Single Output • Up to 92% Efficiency • IP67	MP • 300-2400 Watts • Single & Multi Outputs • Semi F47 Compliant • Status Signals • Extra Power at High Line	DNR120-480 • 120 - 480 Watts • Up to 90% Efficiency • Single Output • Convection-cooled • DC Standby Versions
ECL15 • 15 Watts • 2.5" x 1.25" x 0.96" • Single Output • Class II • Green Mode	+ ECS25 • 25 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	VCT60 • 60 Watts • 4" x 2" x 0.95" • Single Output • Class I • Green Mode	+ ECS100 • 100 Watts • 4" x 2" x 1.2" • Single Output • Class I & II • Green Mode	+ ECM140 • 140 Watts • 5" x 3" x 1.3" • Single Output • 120 W Convection • Signals Options	+ VFT150 Q4 • 150 Watts • 8" x 5" x 1.34" • Single Outputs • Fan Output • Green Mode	+ CCM250 • 250 Watts • 6" x 4" x 1.54" • Single Output • Convection-cooled • 5V Standby	+ PBM300 • 300 Watts • 7.5" x 4.5" x 1.75" • Single & Multi Outputs • Remote On/Off • Mechanical Options	+ SMQ400 • 400 Watts • 8" x 4" x 2" • Single Output • Mechanical Options • Remote On/Off	+ SHP/MHP1000 • 1000 Watts • 9.55" x 5.9" x 2.4" • Single Output • Remote On/Off • Screw Terminals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ VCP15 • 15 Watts • 2.55" x 1.49" x 1.09" • Single Output • Class II • Green Mode	+ ECM40 • 40 Watts • 4" x 2" x 1.2" • Single & Multi Outputs • Class I & II • Convection-cooled	VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67	HPU1K5 • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals	DNR120-960 • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled	
+ ECP40 • 40 Watts • 3" x 2" x 0.9" • Single & Multi Outputs • Class I • Green Mode	+ ECS45 • 45 Watts • 3" x 2" x 0.95" • Single Output • Class I & II • Green Mode	+ VCS70 Q4 • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Green Mode	+ VCS100 Q4 • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Green Mode	+ CLC175 • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options	+ JPS250 • 250 Watts • 8" x 4.2" x 1.51" • Single & Multi Outputs • 200 W Convection • Remote On/Off	SDC320 • 320 Watts • 6" x 4" x 2.14" • Single & Multi Outputs • Status Signals • Remote On/Off	MFA420 • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share	+ GFR1K5 • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I ² C Interface • Current Share & Signals	DLA150 • 150 Watts • 8.8" x 2.6" 1.5" • Single Output • Up to 94% Efficiency • IP67			