

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Switching Brick Power Supply

Name and address of the applicant

XP POWER LTD
401 COMMONWEALTH DR HAW PAR TECHNOCENTRE
LOBBY B, #02-02 149598 SINGAPORE

Name and address of the manufacturer

XP POWER L L C
15641 RED HILL AVE, SUITE 100 TUSTIN CA 92780 UNITED STATES

Name and address of the factory

Note: When more than one factory, please report on page 2

XP POWER (KUNSHAN) LTD
230 BIN NIANG NAN RD ZHANGPU TOWN KUNSHAN
JIANGSU 215321
CHINA Additional Information on page 2

Ratings and principal characteristics

Input: 100-240 Vac, 50/60 Hz, 1.4 A
See Page 2

Trademark (if any)



Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

ALM120PSXXYY-ZZ##V
See Page 2

Additional information (if necessary may also be reported on page 2)

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1(ed.2)

As shown in the Test Report Ref. No. which forms part of this Certificate

E346017-4787976246-1 Correction 1 issued on 2017-08-15

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2017-08-15

Signature:

Original Issue Date: 2017-07-31

Jan-Erik Storgaard



Ref. Certif. No.

DK-65532-M1-UL

Model Details:

ALM120PSXXYY-ZZ##V

(where XX is any number between 12-24 designating output voltage and YY can be blank or "C2" designating Class II configuration, and -ZZ can be blank or "-A", "-6", "-6A", "-8", "-8A" designating AC inlet type, and V can be any alphanumeric or blank designating casing colour)

Models may have an additional ## identifier which can be any alphanumeric or blank designating marketing purposes only.

Factories:

XP POWER INC
990 BENECIA AVE SUNNYVALE CA 94085
UNITED STATES

XP POWER (VIETNAM) CO LTD
LOT D – 4Q – CN MY PHUOC 3 INDUSTRIAL PARK BEN CAT DISTRICT BINH DUONG
VIETNAM

Ratings:

Input: 100-240 Vac, 50/60 Hz, 1.4 A

Output:

ALM120PS12: 12 Vdc (10.1 - 13.5 Vdc), 10 A max., 120W max.;
ALM120PS15: 15 Vdc (13.5 - 17.0 Vdc), 8 A max., 120W max.;
ALM120PS19: 19 Vdc (17.1 - 21.0 Vdc), 6.32 A max., 120W max.;
ALM120PS24: 24 Vdc (21.0 - 26.0 Vdc), 5 A max., 120W max..

Additional Information:

Additionally evaluated to EN 62368-1:2014.

National Difference specified in the CB Test Report.

The original report was modified to include the following changes/additions:

Correct factory name from and update of manufacturer letter.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2017-08-15

Original Issue Date: 2017-07-31

Signature:

Jan-Erik Storgaard