

DK-70363-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) OR SCHEME

CB TEST CERTIFICATE

Product Switching Power Supply

Name and address of the applicant XP POWER LTD

401 COMMONWEALTH DR HAW PAR TECHNOCENTRE

LOBBY B, #02-02

SINGAPORE 149598 SINGAPORE

Name and address of the manufacturer XP POWER L L C

15641 RED HILL AVE

SUITE 100

TUSTIN CA 92780 USA

Name and address of the factory DONGGUAN DONGCHENG ZHUSHAN CINCON

ELECTRONICS FACTORY

Note: When more than one factory, please report on page 2

1 JING XIANG RD DONGCHENG FOREIGN TRADE
INDUSTRIAL PARK ZHUSHAN DONGCHENG DISTRICT

DONGGUAN 523128 GUANGDONG

CHINA

Additional Information on page 2

Ratings and principal characteristics See Page 2

XP

Trademark (if any)

Model / Type Ref. VCE10USXX
See Page 2

Additional information (if necessary may also be reported on page 2)

ed on page 2) Additional Information on page 2

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part
E346017-A9-C of this Certificate

IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1, IEC 60950-1(ed.2);am2

E346017-A9-CB-1 issued on 2018-01-31

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-01-31 Signature:

Jan-Erik Storgaard



DK-70363-UL

Model Details:

VCE10USXX (where XX can be any number 03, 05, 09, 12, 15, 24, 48 designating the output voltage), may also be provided with suffix "-P" optionally for open frame type.

Factories:

CINCON ELECTRONICS CO LTD

8-1 FU KUNG RD FU HSING PARK FU HSING HSIANG CHANGHUA HSIEN 506

TAIWAN

Ratings:

Input Rated: 100-277 Vac, 0.3 A, 50/60 Hz

Output Rated:

Model VCE10US03: Output Rated: 3.3 Vdc (2.95 - 3.65 Vdc), 2.40 A max., 8 W max.; Model VCE10US05: Output Rated: 5 Vdc(4.5 - 5.5 Vdc), 2 A max., 10W max.; Model VCE10US09: Output Rated: 9 Vdc(8.1 - 10 Vdc), 1.11 A max., 10W max.; Model VCE10US12: Output Rated: 12Vdc (10.1 - 13.5 Vdc), 0.83A max., 10W max.; Model VCE10US15: Output Rated: 15Vdc (13.5 - 17 Vdc), 0.67 A max., 10W max.; Model VCE10US24: Output Rated: 24Vdc (21.1 - 26 Vdc), 0.42 A max., 10W max.; Model VCE10US48: Output Rated: 48Vdc (42.1 - 52 Vdc), 0.21 A max., 10W max.

Additional Information:

Additionally evaluated to EN 60950-1:2006/ A11:2009/ A1:2010/ A12:2011/ A2:2013; National Differences specified in the CB Test Report.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupyang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-01-31

Signature: Jan-Erik Storgaard