



Product Service

CERTIFICATE

No. B 065969 0215 Rev. 00

Model(s): DDC4024S05, DDC4024S09, DDC4024S12,
DDC4024S15, DDC4024S24

Brand Name: XP

Parameters:
Rated input voltage: 10-32 Vdc
Rated input current: See below
Rated outputs: See below
Protection class: III
Max. ambient temperature: 50 °C
Degree of protection against ingress of liquids: Ordinary

Remarks:

- 1) When installing, all requirements of below mentioned test standards must be fulfilled.
- 2) The equipment is evaluated for operating in altitude up to 5,000 m above the sea level.

Model-#	Input Rating	Output Rating
DDC4024S05	10-32 Vdc, 3.8 A	5 Vdc, 6 A, 30 W
DDC4024S09	10-32 Vdc, 4.5 A	9 Vdc, 4 A, 36 W
DDC4024S12	10-32 Vdc, 5 A	12 Vdc, 3.4 A, 40 W
DDC4024S15	10-32 Vdc, 5 A	15 Vdc, 2.7 A, 40 W
DDC4024S24	10-32 Vdc, 5 A	24 Vdc, 1.7 A, 40 W

Tested according to: EN 62368-1:2014

Production Facility(ies): 004727

ZERTIFIKAT • CERTIFICATE • 認證證書 • CERTIFICADO • CERTIFICAT