







Product Service

# CERTIFICATE

No. B 057396 0556 Rev. 00

## Technical Considerations:

- The product is intended for use on the following power systems : TN
- The equipment disconnect device is considered to be : N/A - To be provided as an element of the end product.
- The product was submitted and evaluated for use at the maximum ambient temperature (Tma) permitted by the manufacturer's specification of : 50°C for 100% load. 70°C for 50% load (See Enclosure-Miscellaneous: De-rating Curve for additional details)
- The power supply series covered by this report employ Double/Reinforced Insulation between Primary and Secondary circuits.
- Power supplies covered by this report were evaluated for both Class I and Class II (double insulated). Double insulated symbol is optionally provided. See Conditions of Acceptability for insulation required for Class II. Earthing symbol may only be provided for Class I power supplies.
- The unit has two cooling condition: 1) External fan at 10 CFM applied to power supply input side with inward air-flow direction from 5 cm distance between fan and the unit; 2) Convection cooling. The maximum continuous power supply output (Watts) relies on forced air cooling.
- The clearance distances have additionally been assessed for suitability up to 5000 m elevation (1.48 correction factor as per IEC 60664-1, Table A2)

## Engineering Conditions of Acceptability

When installed in an end-product, consideration must be given to the following:

- The following product-line tests are conducted for this product : Electric Strength
- The end-product Electric Strength Test is to be based upon a maximum working voltage of : 2500Vpk (Mains Transient Voltage)
- The following output circuits are at ES1 energy levels : All circuits
- The following output circuits are at PS3 energy levels : All circuits
- The maximum investigated branch circuit rating is : 16 A
- The investigated Pollution Degree is : 2
- Proper bonding to the end-product main protective earthing termination is: Required when installed in a Class I end product.
- The following end-product enclosures are required : Fire, Electrical, Mechanical
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJ2 insulation system with the indicated rating greater than Class A (105°C) : TR1 - Class B (130)
- The power supply was evaluated to be used at altitudes up to : "5,000 m

**Tested according to:** EN 62368-1:2014/A11:2017

**Production Facility(ies):** 003227, 071712, 089850