



Product Service

CERTIFICATE

No. B 057396 0437 Rev. 03

Holder of Certificate: **XP Power LLC.**
340 Commerce, Suite 100
Irvine CA 92602
USA

Certification Mark:



Product: **Power supply**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 7191329786-13-TR

Valid until: 2026-01-07

Date, 2024-06-07

(Kim Hock Teo)

CERTIFICATE

No. B 057396 0437 Rev. 03

Model(s): GCS265PS24-XD0642,
GCS265PS12-C-XT1761,
GCS265PSxxyy

Where xx is between 12-56, yy is "-C", "-TF", "-EF" or blank. May also be provided with additional suffix "SF", "S" or "R". All "-" considered optional.

Brand Name: XP

Parameters:

Rated Input Voltage: 100-240 VAC

Rated Frequency: 50/60 Hz

Rated Input Current: 3.0 A

Protection Class: Class I or Class II at end use

Elevation for Use: 0-5000 m above sea level

CERTIFICATE

No. B 057396 0437 Rev. 03

Approved models and Rated Outputs:

Model Number	DC OUTPUT (with 7 CFM Forced Cooling)				
	V1 Voltage (V)	Current (A)	V2 Voltage (V)	Max Current (A)	Total Power (W)
GCS265PS12	10.1-13.5	20.8	5	3	265
GCS265PS12 -C-XT1761	10.1-13.5	20.8	5	3	265
GCS265PS15	13.6-17	16.66	5	3	265
GCS265PS18	17.1-21	13.9	5	3	265
GCS265PS24	21.1-26	10.4	5	3	265
GCS265PS28	26.1-31	8.9	5	3	265
GCS265PS33	31.1-33	7.6	5	3	265
GCS265PS36	33.1-42	6.94	5	3	265
GCS265PS48	42.1-54	5.2	5	3	265
GCS265PS56	54.1-63.2	4.5	5	3	265
GCS265PS24 -XD0642	24	7.5	5	3	195

NOTE: V2 IS THE 5VDC STANDBY OUTPUT

SUFFIX:
 C: PROVIDED WITH COVER,
 TF: PROVIDED WITH TOP FAN,
 EF: PROVIDED WITH END FAN,
 MODELS WITHOUT SUFFIX "C", "TF" OR "EF" ARE OPEN FRAME MODELS (WITHOUT COVER).
 SF: PROVIDED WITH SINGLE POLE FUSING,
 S: PROVIDED WITH SCREW TERMINAL BLOCK,
 R: REMOTE INHIBIT.

CERTIFICATE

No. B 057396 0437 Rev. 03

Output Power under different configurations:

Model Number	Convictional Cooling Without Cover		Convictional Cooling With Cover		Forced Air Cooling With Cover	
	Max Output @50°C	Max Output @70°C	Max Output @50°C	Max Output @70°C	Max Output @50°C	Max Output @70°C
GCS265PS12	V1:180W, 15A V2: 10W, 2A	V1: 90W, 7.5A V2: 5W, 1A	V1: 140W, 11.67A V2: 10W, 2A	V1: 70W, 5.83A V2: 5W, 1A	V1: 250W, 20.8 V2: 15W, 3A	V1: 125W, 10.4A V2: 7.5W, 1.5A
GCS265PS15	V1:180W, 12A V2: 10W, 2A	V1: 90W, 6A V2: 5W, 1A	V1: 140W, 9.33A V2: 10W, 2A	V1: 70W, 4.67A V2: 5W, 1A	V1: 250W, 16.7A V2: 15W, 3A	V1: 125W, 8.3A V2: 7.5W, 1.5A
GCS265PS18	V1:180W, 10A V2: 10W, 2A	V1: 90W, 5A V2: 5W, 1A	V1: 140W, 7.78A V2: 10W, 2A	V1: 70W, 3.89A V2: 5W, 1A	V1: 250W, 13.9A V2: 15W, 3A	V1: 125W, 6.9A V2: 7.5W, 1.5A
GCS265PS24	V1: 180W, 7.5A V2: 10W, 2A	V1: 90W, 3.75A V2: 5W, 1A	V1: 140W, 5.83A V2: 10W, 2A	V1: 70W, 2.92A, V2: 5W, 1A	V1: 250W, 10.4A V2: 15W, 3A	V1: 125W, 5.2A V2: 7.5W, 1.5A
GCS265PS28	V1: 180W, 6.4A V2: 10W, 2A	V1: 90W, 3.21A V2: 5W, 1A	V1: 140W, 5A V2: 10W, 2A	V1: 70W, 2.5A, V2: 5W, 1A	V1: 250W, 8.9A V2: 15W, 3A	V1: 125W, 4.5A V2: 7.5W, 1.5A
GCS265PS33	V1: 180W, 5.5A V2: 10W, 2A	V1: 90W, 2.72A V2: 5W, 1A	V1: 140W, 4.24A V2: 10W, 2A	V1: 70W, 2.12A, V2: 5W, 1A	V1: 250W, 7.6A V2: 15W, 3A	V1: 125W, 3.8A V2: 7.5W, 1.5A
GCS265PS36	V1: 180W, 5A V2: 10W, 2A	V1: 90W, 2.5A V2: 5W, 1A	V1: 140W, 3.89A V2: 10W, 2A	V1: 70W, 1.94A, V2: 5W, 1A	V1: 250W, 6.9A V2: 15W, 3A	V1: 125W, 3.5A V2: 7.5W, 1.5A
GCS265PS48	V1: 180W, 3.75A V2: 10W, 2A	V1: 90W, 1.875A V2: 5W, 1A	V1: 140W, 2.92A V2: 10W, 2A	V1: 70W, 1.46A V2: 5W, 1A	V1: 250W, 5.2A V2: 15, 3A	V1: 125W, 2.6A V2: 7.5W, 1.5A
GCS265PS56	V1: 180W, 3.2A V2: 10W, 2A	V1: 90W, 1.61A V2: 5W, 1A	V1: 140W, 2.5A V2: 10W, 2A	V1: 70W, 1.25A V2: 5W, 1A	V1: 252W, 4.5A V2: 15W, 3A	V1: 125W, 2.23A V2: 7.5W, 1.5A

Model Number	With End Fan		With Top Fan		Forced Air Cooling Without Cover	
	Max Output @50°C	Max Output @70°C	Max Output @50°C	Max Output @70°C	Max Output @50°C	Max Output @70°C
GCS265PS12	V1: 250W, 20.8A V2: 15W, 3A	V1: 125W, 10.4A V2: 7.5W, 1.5A	V1: 250W, 20.8A V2: 15W, 3A	V1: 125W, 10.4A V2: 7.5W, 1.5A	V1: 250W, 20.8A V2: 15W, 3A	V1: 125W, 10.4A V2: 7.5W, 1.5A
GCS265PS15	V1: 250W, 16.7A V2: 15W, 3A	V1: 125W, 8.3A V2: 7.5W, 1.5A	V1: 250W, 16.7A V2: 15W, 3A	V1: 125W, 8.3A V2: 7.5W, 1.5A	V1: 250W, 16.7A V2: 15W, 3A	V1: 125W, 8.3A V2: 7.5W, 1.5A
GCS265PS18	V1: 250W, 13.9A V2: 15W, 3A	V1: 125W, 6.9A V2: 7.5W, 1.5A	V1: 250W, 13.9A V2: 15W, 3A	V1: 125W, 6.9A V2: 7.5W, 1.5A	V1: 250W, 13.9A V2: 15W, 3A	V1: 125W, 6.9A V2: 7.5W, 1.5A
GCS265PS24	V1: 250W, 10.4A V2:15W, 3A	V1: 125W, 5.2A, V2: 7.5W, 1.5A	V1: 250W, 10.4A V2:15W, 3A	V1: 125W, 5.2A V2: 7.5W, 1.5A	V1: 250W, 10.4A V2:15W, 3A	V1: 125W, 5.2A V2: 7.5W, 1.5A
GCS265PS28	V1: 250W, 8.9A V2:15W, 3A	V1: 125W, 4.5A, V2: 7.5W, 1.5A	V1: 250W, 8.9A V2:15W, 3A	V1: 125W, 4.5A V2: 7.5W, 1.5A	V1: 250W, 8.9A V2:15W, 3A	V1: 125W, 4.5A V2: 7.5W, 1.5A
GCS265PS33	V1: 250W, 7.6A V2:15W, 3A	V1: 125W, 3.8A, V2: 7.5W, 1.5A	V1: 250W, 7.6A V2:15W, 3A	V1: 125W, 3.8A V2: 7.5W, 1.5A	V1: 250W, 7.6A V2:15W, 3A	V1: 125W, 3.8A V2: 7.5W, 1.5A
GCS265PS36	V1: 250W, 6.9A V2:15W, 3A	V1: 125W, 3.5A, V2: 7.5W, 1.5A	V1: 250W, 6.9A V2:15W, 3A	V1: 125W, 3.5A V2: 7.5W, 1.5A	V1: 250W, 6.9A V2:15W, 3A	V1: 125W, 3.5A V2: 7.5W, 1.5A
GCS265PS48	V1: 250W, 5.2A V2: 15W, 3A	V1: 125W, 2.6A V2: 7.5W, 1.5A	V1: 250W, 5.2A V2: 15W, 3A	V1: 125W, 2.6A V2: 7.5W, 1.5A	V1: 250W, 5.2A V2: 15W, 3A	V1: 125W, 2.6A V2: 7.5W, 1.5A
GCS265PS56	V1: 252W, 4.5A V2: 15W, 3A	V1: 125W, 2.23A V2: 7.5W, 1.5A	V1: 252W, 4.5A V2: 15W, 3A	V1: 125W, 2.25A V2: 7.5W, 1.5A	V1: 252W, 4.5A V2: 15W, 3A	V1: 125W, 2.23A V2: 7.5W, 1.5A

V2: 5V Standby Output

CERTIFICATE

No. B 057396 0437 Rev. 03

Conditions of Acceptability:

When installing the equipment, all requirements of the standards and the manufacturer's specifications must be met.

The models require:

- A suitable electrical and fire enclosure must be provided in the end use equipment.
- The product is intended for use on the following power systems: TN.
- The following output circuits are at ES1 energy levels: All.
- The following output circuits are at PS3 energy levels: All.
- Sufficient clearance and creepage distance shall be provided between the primary circuit and accessible conductive parts.
- Heatsinks are floating and considered live. They shall not be accessible in the end product.
- Proper bonding to the end-product main protective earthing terminal is required when installed in Class I end product, ground bond test shall be conducted.
- Touch current test and dielectric Strength test need to be considered at end use equipment.
- The power supplies have a fuse in the neutral of the primary circuit. A warning for service persons to be considered in the end product.

Tested according to: EN 62368-1:2014/A11:2017